



Manual of Recommended Practice for Railway Engineering and Maintenance of Way

By American Railway Association

RareBooksClub. Paperback. Book Condition: New. This item is printed on demand. Paperback. 68 pages. Dimensions: 9.7in. x 7.4in. x 0.1in. This historic book may have numerous typos and missing text. Purchasers can download a free scanned copy of the original book (without typos) from the publisher. Not indexed. Not illustrated. 1907 edition. Excerpt: . . . must be taken that the clips and the sides of the briquette be clean and free from grains of sand or dirt which would prevent a good bearing. The load should be applied at the rate of 600 lbs. per minute. The average of the briquettes of each sample tested should be taken as the test, excluding any results which are manifestly faulty. CONSTANCY OF VOLUME. Method. 48-Tests for constancy of volume are divided into two classes: (1) Normal tests, or those made in either air or water maintained at about 21 C. (700 F.), and (2) accelerated tests, or those made in air, steam or water at a temperature of 45 C. (115 F.) and upward. The test pieces should be allowed to remain 24 hours in moist air before immersion in water or steam, or preservation in air. 49. For these...



READ ONLINE
[4.24 MB]

Reviews

An exceptional ebook along with the font applied was interesting to read through. it was actually writtern really completely and beneficial. Once you begin to read the book, it is extremely difficult to leave it before concluding.

-- **Mr. Hector Cole Jr.**

This written pdf is wonderful. It can be writter in easy phrases and not difficult to understand. Your lifestyle span will likely be enhance once you full looking over this ebook.

-- **Juanita Reynolds**